



ECB – 3610S

Wireless Multi-Client Bridge/AP/WDS



2.4 GHz

802.11 b/g

54 Mbps

ECB-3610S Wireless High Power and High Gain Client Bridge/Access Point/ WDS (wireless distribution system) operates in the 2.4 GHz frequency spectrum supporting the 802.11b (2.4GHz, 11Mbps) and the newer, faster 802.11g (2.4GHz, 54Mbps) wireless standards. It's the best way to add wireless capability to your existing wired network, or to add bandwidth to your wireless installation.



To protect your wireless connectivity, it can encrypt all wireless transmissions through 64/128-bit WEP data encryption and also supports WPA. The MAC address filter lets you select exactly which stations should have access to your network. With the Wireless Multi-Client Bridge/Access Point/WDS, you'll experience the best wireless connectivity available today

Features	Benefits
High Speed Data Rate Up to 54Mbps	Capable of handling heavy data payloads such as MPEG video streaming
High Output Power up to 28dBm	Excellent output power spreads the operation distance
IEEE 802.11b/g Compliant	Fully Interoperable with IEEE 802.11b/IEEE802.11g compliant devices
Point-to-point, Point-to-multipoint Wireless Connectivity	Let users transfer data between two buildings or multiple buildings
WPA/WPA2/ IEEE 802.1x support	Powerful data security
Hide SSID (AP Mode)	Avoids unallowable users sharing bandwidth, increases efficiency of the network
DHCP Client/ Server	Simplifies network administration
WDS (Wireless Distributed System)	Make wireless AP and Bridge mode simultaneously as a wireless repeater
MAC address filtering (AP Mode)	Ensures secure network connection
Power-over-Ethernet (IEEE802.3af)	Flexible Access Point locations and cost savings
Layer 2 isolation (AP mode)	Improved the security of each client

*** Subject to change without prior notice



ECB – 3610S

Wireless Multi-Client Bridge/AP/WDS



2.4 GHz

802.11 b/g

54 Mbps

Technical Specifications

Data Rates

1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54 Mbps

Standards

IEEE802.11b/g, IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.1f, IEEE802.1x

Compatibility

IEEE 802.11g/ IEEE 802.11b

Power Requirements

Power Supply: 90 to 240 VDC \pm 10% (depends on different countries)
Device: 12 V/ 1A

Status LEDs

LAN: Link, WLAN: Link, Power: on/off

Regulation Certifications

FCC Part 15 B & C,
CE: EN 300328, EN 301489
EN 60950

RF INFORMATION

Frequency Band

802.11b/g: U.S., Europe and Japan product covering 2.4 to 2.484 GHz, programmable for different country regulations

Media Access Protocol

Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA)

Modulation Technology

Orthogonal Frequency Division Multiplexing (OFDM)
DBPSK @ 1Mbps
DQPSK @2Mbps
CCK @ 5.5 & 11Mbps
BPSK @ 6 and 9 Mbps
QPSK @ 12 and 18 Mbps
16-QAM @ 24 and 36 Mbps
64-QAM @ 48 and 54 Mbps

Operating Channels

11 for North America
14 for Japan
13 for Europe

Receive Sensitivity (Typical)

802.11g:

-90 dBm @ 6Mbps,
-74 dBm @ 54Mbps

802.11b:

-95 dBm @ 1Mbps -90 dBm @ 11Mbps

Available Transmit Power

(Typical)

- 2.4~2.462G(IEEE802.11g)

27dBm @6 ~ 24Mbps

25dBm@36Mbps

24 dBm@48Mbps

23dBm@54Mbps

- 2.4~2.462G(IEEE802.11b)

28dBm. @1, 2, 5.5 and 11Mbps

RF Connector

TNC Type (Female Reverse)

NETWORKING

Topology

Ad-Hoc, Infrastructure

Operation Mode

Point-to-Point/ Point-to-Multipoint
Bridge/ AP/ Client Bridge/ WDS

Interface

One 10/100Mbps RJ-45 LAN Port

Security

- IEEE802.1x Authenticator / RADIUS Client (EAP-MD5/TLS/TTLS) Support in AP Mode
- IEEE802.1x Supplicant (EAP-MD5/TLS/TTLS, PEAP) support in Client Bridge Mode
- WPA /WPA2/ Pre Share KEY (PSK) with TKIP/AES
- MAC address filtering (AP only)
- Hide SSID in beacons
- VLAN Pass-through
- L2 Isolation

IP Auto-configuration

DHCP client/server

MANAGEMENT

Configuration

Web-based configuration (HTTP)
Telnet Configuration
SNMP V1, V2c, MIB&II

Firmware Upgrade

Upgrade firmware via web-browser

ENVIRONMENTAL

Temperature Range

Operating: 0°C to 45°C (32°F to 113°F)
Storage: -20°C to 70°C (-4°F to 158°F)

Humidity (non-condensing)

5%~95% Typical

Package Contents

One AP/ CB Device
One TNC Dipole Antenna
One Power Adapter
One CAT5 UTP Cable
One Quick Start Guide
One CD-ROM with User's Manual

*** Subject to change without prior notice

EnGenius Networks Singapore Pte Ltd

215 Henderson Road #01-04 Henderson Industrial Park Singapore 159554

Tel: +65-62271088 Fax: +65-62272766

Website: www.engeniustech.com.sg Email: inquiry@engeniustech.com.sg