

This is a dual-radio High Power and High Gain Access Point/Client Bridge that operates seamlessly in the 2.4 GHz/5 GHz frequency spectrum and the newer, faster 802.11a (5GHz, 54Mbps) and 802.11g (2.4GHz, 54Mbps) wireless standards. It's the best way to add wireless capability to your existing wired network, or to add bandwidth to your wireless installation.

To protect your wireless connectivity, it can encrypt all wireless transmissions through 64/128-bit WEP data encryption and also supports WPA. The MAC address filter lets you select exactly which stations should have access to your network. With the Wireless Multi-Client Bridge/Access Point/WDS, you will experience the best wireless connectivity available today.



Features	Benefits
High Speed Data Rate Up to 54Mbps	Capable of handling heavy data payloads such as MPEG video streaming
E.I.R.P up to 36 dBm (with 16dBi Antenna Gain) for Band C, 11a (IR2007 compliant)	Excellent output power spreads the operation distance
IEEE 802.11a/b/g compliant	Fully Interoperable with IEEE802.11a / IEEE 802.11b / IEEE802.11g compliant devices
Point-to-point, Point-to-multipoint Wireless Connectivity	Let users transfer data between two buildings or multiple buildings
WPA/WPA2/ IEEE 802.1x support	Powerful data security
WDS (Wireless Distribution System)	Make wireless AP and Bridge mode simultaneously as a wireless repeater
Hide SSID (AP Mode)	Avoids unallowable users sharing bandwidth, increases efficiency of the network
DHCP Client/ Server	Simplifies network administration
Watertight and Weatherproof (IP67)	Avoid water invaded and weather corroded
Wide temperature range and robust mechanical design	Delivers reliable, top performance in the most demanding environments
Power-over-Ethernet (IEEE802.3af Compliant)	Flexible Access Point locations and cost savings

\*\* Subject to change without prior notice

## Technical Specifications

### Data Rates

1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, 54 Mbps

### Standards

IEEE802.11a/b/g, IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.1f, IEEE802.1x

### Compatibility

IEEE 802.11g/ IEEE 802.11b

### Power Requirements

Active Ethernet (Power over Ethernet) –48 VDC/0.375A

External Unit: Auto sensing 100/240 VAC; 50/60 Hz

### Regulation Certifications

FCC Part 15/UL, ETSI 300/328/CE  
Conforms to Ofcom IR2007

## RF INFORMATION

### Frequency Band

**802.11a Band C:** 5.725~5.825GHz

**802.11b/g:** U.S., Europe and Japan product covering 2.4 to 2.484 GHz, programmable for different country regulations

### Media Access Protocol

Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA)

### Modulation Technology

Orthogonal Frequency Division Multiplexing (OFDM)  
DBPSK @ 1Mbps  
DQPSK @2Mbps  
CCK @ 5.5 & 11Mbps  
BPSK @ 6 and 9 Mbps  
QPSK @ 12 and 18 Mbps  
16-QAM @ 24 and 36 Mbps  
64-QAM @ 48 and 54 Mbps

### Operating Channels

**802.11b/g:**

11 for North America, 14 for Japan, 13 for Europe,  
2 for Spain, 4 for France

**802.11a:**

UK:4 non-overlapping channel (5.74~5.825GHz)

### Receive Sensitivity (Typical)

- 5.15~5.85G(IEEE802.11a)  
6Mbps@ -88dBm;  
54Mbps@ -70dBm
- 2.412~2.472G(IEEE802.11g)  
6Mbps@ -91dBm;  
54Mbps@ -74dBm
- 2.412~2.472G(IEEE802.11b)  
11Mbps@ -90dBm  
1Mbps@ -95dBm

### Available transmit power (Typical)

- 5.745~5.85GHz (IEEE802.11a)  
20dBm @6 ~ 24Mbps  
18dBm @36Mbps  
16dBm @48Mbps  
15dBm @54Mbps
- 2.412~2.472G(IEEE802.11g)  
27dBm @6 ~ 24Mbps  
25dBm@36Mbps  
24 dBm@48Mbps  
23dBm@54Mbps
- 2.412~2.472G(IEEE802.11b)  
28dBm. @1, 2, 5.5 and 11Mbps

### Antenna

802.11a: Embedded patch antenna  
16dBi (5GHz)  
802.11b/g: SMA connector 5dBi (2.4GHz)

## NETWORKING

### Topology

Ad-Hoc, Infrastructure

### Operation Mode

Point-to-Point/ Point-to-Multipoint  
Bridge/ AP/ Client Bridge/ WDS

### Interface

Wireless IEEE802.11b/g  
One 10/100 RJ-45 port

### Security

- ⌘ IEEE802.1x Authenticator RADIUS Client (EAP-MD5/TLS/TTL) Support in AP Mode
- ⌘ IEEE802.1x Supplicant (EAP-MD5/TLS/TTL, PEAP) support in Client Bridge Mode
- ⌘ WPA /WPA2/ Pre Share KEY (PSK) with TKIP/AES
- ⌘ MAC address filtering (AP only)
- ⌘ Hide SSID in beacons

### IP Auto-configuration

DHCP client/server

## MANAGEMENT

### Configuration

Web-based configuration (HTTP)  
Telnet Configuration  
SNMP V1,

### Firmware Upgrade

Upgrade firmware via web-browser  
Serial Interface (RS-232)

## PHYSICAL

### Dimensions (HxWxD)

163.8(L)mm \* 135.2(W)mm \*  
47.0(H)mm

### Weight

1.2 Kg (2.6 lbs)

## ENVIRONMENT

### Temperature Range

Operating: 0°C to 65  
Storage: -40°C to 80°

### Humidity (non-condensing)

5%~95% Typical

\*\*\* Subject to change without prior notice