

Quick set up for the 3G-M1_ROUTER

Slide off the cover and insert your sim card into the slot, replace the cover and connect the dongle to a suitable power supply, eg a USB port on a computer or a USB car charger. (NB This is not a 3G dongle, USB is used to power the device only). For most UK networks the router should connect automatically and show a steady blue light if connected at 3G. You can then connect either with a cable or wirelessly, default SSID is M1_XXXXXX, the password is on the label on the device.

If you need to enter an APN manually you need to connect either with a cable or wirelessly, open your web browser and enter the IP address **192.168.100.1**

Username: **admin**

Password: **admin**

M1 3G WIRELESS ROUTER

The screenshot displays the web interface for the M1 3G Wireless Router. The left sidebar shows a navigation menu with categories like Wizard, 3G ROUTER, Status, WAN Side Info, Device Info, User Side Info, Network, LAN Settings, IP-MAC Binding, Static Route, WLAN, Basic Settings, Security Settings, Advanced Settings, Security, Application, and Manage. The main content area is titled "Network > Internet Settings" and contains the following configuration sections:

- WAN Mode Select:** Radio buttons for 3G Mode (selected), Wire Mode, and Wireless Client Mode.
- Connection Settings:** A table of fields for configuring the connection:

Operator	AUTO	APN Info
WAN Select	AUTO	
Dial Number	*99#	
APN	orangeinternet	
User Name		
Password		
pin code		
Auth Type	AUTO	
Operation Mode	Keep Alive	
Redial Period	5	seconds
Idle Time	600	seconds
- WAN MAC Clone:** A dropdown menu set to "Disable".

At the bottom of the form are "Apply" and "Cancel" buttons.

Click on Network then Internet settings and fill in the dial number, APN and username and password as supplied by your network provider. You can also change the WIFI settings here, click on WLAN, and change the SSID in Basic Settings and change the password in the Security Settings.