



HSPA+ Outdoor Router RUT700 Router

Teltonika RUT700 is outdoor 3G router with high speed wireless and Ethernet connections. Internal HSPA+ modem can reach download rate of up to 21Mbps. Router supports the latest IEEE802.11n as well as IEEE802.11b/g standards and provides wireless receiving and transmitting rate of up to 150 Mbps. High gain directional antenna 3G antenna allows the router to be used in low signal locations while external Wi-Fi connector makes it possible to attach desired antenna. IEEE 802.3af-2003 compliant POE uses single Ethernet cable to communicate with the device and to power it making for an easy installation.

Key Features

- Downlink of 21 Mbps
- Uplink of 5.76Mbps
- Complies with IEEE 802.11n, IEEE 802.11g, IEEE 802.11b wireless standards
- Complies with IEEE 802.3 and IEEE 802.3u standards
- IEEE 802.3af-2003 compliant POE
- One 10/100 Base-T Ethernet port
- Adjustable pole mounting kit
- Waterproof RJ45 socket
- Secure SIM card socket
- Dual-polarization 6/8 dBi MIMO antenna
- Integrated OpenVPN, IPSec and SNMP
- SMS reboot, Status via SMS functions



UMTS/GSM Specifications

UMTS

- 850/900/AWS1700/1900/2100 MHz
- HSDPA mode: 21 Mbps (Cat 14) downlink speed
- HSUPA mode: 5.76 Mbps (Cat 6) uplink speed
- UMTS mode: 384 kbps DL/384 kbps UL
- 6/8 dBi MIMO GSM/UMTS antenna

GSM/GPRS/EDGE

- 850/900/1800/1900 MHz
- Power Class 4 (2 W, 33 dBm) GSM/GPRS 850/900 MHz
- Power Class 1 (1 W, 30 dBm) GSM/GPRS 1800/1900 MHz
- Power Class E2 (0.5 W, 27 dBm) for EDGE 850/900 MHz
- Power Class E2 (0.4 W, 26 dBm) for EDGE 1800/1900 MHz
- GSM: 14.4 kbps DL/14.4 kbps UL
- GPRS: 107 kbps DL/85.6 kbps UL (class 33)
- EDGE: 296 kbps DL/236.8 kbps UL (class 33)

Specifications

LAN and Wi-Fi

- High performance 320 MHz CPU with 256 Mbits SDRAM
- IEEE 802.11b/g/n, IEEE 802.3, IEEE 802.3u standards
- IEEE 802.3af-2003 compliant POE
- 64/128-bit WEP, WPA, WPA2, WPA&WPA2 encryption methods
- 1x LAN 10/100Mbps Ethernet port
- Supports Auto MDI/MDIX
- Remote/local Web management
- 1x RP-SMA Wi-Fi antenna connector
- SSID stealth mode and access control based over MAC address
- System log to record the status of the Router
- Auto negotiation/manual mode for IEEE 802.11b/g/n
- Dynamic DNS
- LAN access control over Internet connection
- Virtual server
- Auto wireless channel selection
- OpenVPN, IPSec, SNMP
- SMS and Ping reboot, Status via SMS
- 1 x LAN LED

Electrical, Mechanical & Environmental

- | | |
|--------------------------|--|
| • Dimensions (H x W x D) | 290mm x 240mm x 45mm |
| • Weight | 1.3kg |
| • Power supply | 36 – 57VDC POE adapter |
| • Power consumption | < 7W |
| • Antenna connectors | 1 x RP-SMA for Wi-Fi |
| • Indicators | 1 x Power LED, 1 x LAN LED, 1 x Status LED |
| • Operating temperature | -20° to 50° C |
| • Storage temperature | -20° to 70° C |
| • Operating humidity | 10% to 90% Non-condensing |
| • Storage humidity | 5% to 95% Non-condensing |

TELTONIKA JSC
Saltoniskiu str.10C,LT08105
Vilnius, Lithuania
Phone: +370 5 265 73 60
Fax: +370 5 276 13 80
info@teltonika.lt
www.teltonika.lt