

ENS500EXT

Long Range Wireless 11N Outdoor AP /CB

- 2T+2R
- 11a/n
- 300Mbps
- High performance



PRODUCT OVERVIEW

ENS500EXT Wireless Outdoor unit provides not only external antenna connectors for antenna upgrade, but also high output power and high sensitivity can extend the transmission range to deliver a stable wireless connection. ENS500EXT integrates 4 operation modes: Access Point, Client Bridge, Client Router and WDS.

Advanced multi-function operation modes offer flexibility in constructing scalable wireless networks for all possible applications. ENS500EXT is designed to deliver reliable service under harsh outdoor environment with certified IP65 protection and tailored to accommodate multimedia streaming services with data-rate up to 300Mbps. Most importantly, it is built-in encryption standards (WEP, WPA, WPA2, TKIP/AES and IEEE802.1x) ensure maximum security and compatibility.

FEATURES	
HARDWARE FEATURES	
High output power	Transmit high output power programmable for different country selections
High Data Rate	High speed transmitting rate up to 300Mbps with 2T2R 802.11n
Long range transmitting	Transmit power control and distance control (ACK timeout)
Signal Strength Display	Indicate RF signal strength to be shown as LEDs of 3 colors, making network build-up easier. LED indicators have the best transmit and receive signal for traffic communication
PoE Support	Support proprietary 24V passive power over Ethernet
SOFTWARE	
Multiple SSID	4 SSID supported. Each SSID can set itself wireless or WAN access setting
PPPoE	Point-to-Point Protocol over Ethernet at Client Router mode. This function will keep trying when failed or disconnected
PPTP	Point-to-Point Tunneling Protocol (PPTP) is a method for implementing virtual private networks
VLAN Pass-through	Support VLAN Pass-through
Firmware Upgrade	Upgrading firmware via web browser, setting are reserved after upgrade
Reset & Backup	Reset to factory default. User can export all setting into a file via WEB
Ping & Trace Route	Built-in PING function & Trace Route function in Web GUI
MIB	MIB I, MIB II (RFC1213), Private MIB
SNMP	V1, V2c, V3

SPECIFICATIONS	
HARDWARE SPECIFICATIONS	
MCU	Atheros AR9344
RF	N/A
Memory	64MB
Flash	16MB
Physical Interface	2 x RJ-45 for 10/100 Fast Ethernet 1 x Reset Button

Power Requirements	<ul style="list-style-type: none"> - Active Ethernet (Power over Ethernet) - Proprietary PoE design - Power Adapter 24V / 0.6A 			
RF SPECIFICATIONS				
Frequency Band	802.11a/n			
Data rate	300Mbps			
Radio Frequency Band (The Max. Power may be different depending on local regulations)	Channel	Data Rate	Tx Avg. Power (±2dBm)	Rx Sensitivity (±2dBm)
		6Mbps	26	-95
	802.11a (5.18 ~ 5.825GHz)	9Mbps	26	-92
		12Mbps	26	-89
		18Mbps	26	-85
		24Mbps	26	-81
		36Mbps	25	-79
		48Mbps	23	-76
		54Mbps	21	-75
	802.11n (5.18 ~ 5.825GHz)	MCS0 / MCS8	26	-95
		MCS1 / MCS9	26	-93
		MCS2 / MCS10	26	-90
		MCS3 / MCS11	26	-87
		MCS4 / MCS12	24	-84
		MCS5 / MCS13	23	-79
MCS6 / MCS14		22	-75	
MCS7 / MCS15	21	-73		
Antenna	2xExternal SMA Connector			
SOFTWARE SPECIFICATIONS				
Operation Mode	Access Point / Client Bridge / Client Router / WDS			

Wireless/Network	<p>Auto Channel Selection (Setting varies by Regular Domains)</p> <p>Obey Regulatory Power</p> <p>Distance Control (802.1x Ack timeout)</p> <p>CLI Supported</p> <p>802.1x Supplicant (CB Mode)</p> <p>Multiple SSID (4 SSID), BSSID</p> <p>WDS AP / WDS Bridge / WDS Station</p> <p>Multicast Supported</p> <p>RADIUS Accounting</p> <p>VLAN Tag / VLAN Pass-through</p> <p>Auto Reboot</p> <p>WiFi Scheduling</p>
Security	<p>WEP Encryption-64/128/152 bit</p> <p>WPA/WPA2 Personal (WPA-PSK using TKIP or AES)</p> <p>WPA/WPA2 Enterprise (WPA-EAP using TKIP)</p> <p>Hide SSID in beacons</p> <p>MAC address filtering, up to 50 field</p> <p>Wireless STA (Client) connected list</p>
QoS	WMM

ENVIRONMENT AND MECHANICAL	
Temperature Range	Operating -20°C~70°C Storage -30°C to 80°C
Humidity (non-condensing)	0%~90% typical
Dimensions	186mm (L) x 100mm (W) x 29mm (H)
Weight	300g

PACKAGE CONTENT
▶ 1 x ENS500EXT
▶ 2 x 5GHz 5dBi Omni Antenna
▶ 1 x Power Adapter (24V/0.6A)
▶ 1 x PoE Injector (EPE1212)
▶ 1 x Pole Mount Set
▶ 1 x Screw Set
▶ 1 x Technical Support Card