

EOC-2610 is a long range outdoor wireless Access Point / Client Bridge that operates seamlessly in the 2.4GHz frequency spectrum and provides high bandwidth up to 108Mbps with Super G. It features high transmitted output power and high receivable sensitivity. High output power and high sensitivity can extend range and coverage to reduce the roaming between Access Points to get a more stable wireless connection. It also reduces the expense of equipment in the same environment.

It supports distance control by 1km to 30km and RSSI indicator which enables the best transmit and receive signals for traffic communication. This product comes with PoE injector for building in outdoor environment easily.

To protect your wireless connectivity, it can encrypt all wireless transmissions through 64/128-bit WEP data encryption and also supports WPA/WPA2. The MAC address filter lets you select exactly which stations should have access to your network. In addition, the User Isolation function can protect the private network between client users.

The attractive design, high performance, and array of features make EOC-2610 a suitable wireless solution for your residence or office.



### Package Content

- ① 1\* 802.11b/g Long range AP/CB (EOC-2610)
- ① 1\* PoE Injector (EPE-1212)
- ① 1\* Power Adaptor
- ① 1\* CD with User's Manual
- ① 1\* QIG
- ① 1\* Metal strap
- ① 1\* Special screw set

\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

## Features

### Wireless

- **2.4GHz** It works in 2.4GHz frequency spectrum
- **High output power** Transmit output power programmable for different country selections
- **High Data Rate** High speed transmitting rate up to 108Mbps with Super G, support large payload such as MPEG video streaming
- **Multifunction application** Access Point/Client Bridge/Client Router
- **Long range transmitting** Transmit power control and distance control (ACK timeout)
- **Signal Strength** LED indicators have the best transmit and receive signal for traffic communication

### Networking

- **Public wireless solution** An AP interface that is especially useful in public areas such as hotspots and enterprise
- **Signal Strength Display** RF signal strength status shown LEDs of 3 colors, making network build-up easier
- **QoS(WMM)** Enhance performance and density

### Security

- **802.11i** WEP, WPA, WPA2 (Encryption support TKIP/AES)
- **MAC address functions** MAC address filter (AP mode)
- **802.1x** IEEE802.1x Authencatior
- **L2 isolation**
- **Station isolation**

### Management

- **Firmware Upgrade** Upgrading firmware via web browser, setting are reserved after upgrade
- **Reset & Backup** Reset to factory default. User can export all setting into a file via WEB
- **MIB** MIB I, MIB II(RFC1213)
- **SNMP** V1, V2c

\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

## Technical Specifications

<b>Hardware Specification</b>	
Physical Interface	One 10/100 Fast Ethernet RJ-45 Reset Button One SMA Connector One switch (external and internal antenna switching)
LED indicators	Power/ Status LAN (10/100Mbps) WLAN (Wireless is up) 3 x Link Quality (Client Bridge mode) <ul style="list-style-type: none"> <li><span style="color: green;">●</span> Green: Good Quality</li> <li><span style="color: yellow;">●</span> Yellow: Marginally Acceptable Quality</li> <li><span style="color: red;">●</span> Red: Bad Quality</li> </ul>
Power Requirements	Active Ethernet (Power over Ethernet) Proprietary PoE design Power Adapter 24V / 0.8A DC
Regulation Certifications	FCC Part 15C/15B, EN 300 328/EN 301 489-1/-17

<b>RF Specification</b>							
Frequency Band	<b>802.11b/g</b> 2.412~2.472GHz						
Modulation Technology	OFDM = BPSK, QPSK, 16-QAM, 64-QAM DSSS = DBPSK, DQPSK, CCK						
Operating Channels	<b>802.11b/g</b> 11 for North America, 14 for Japan, 13 for Europe						
Receive Sensitivity (Typical)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"><b>802.11g</b></td> <td style="width: 50%;"><b>802.11b</b></td> </tr> <tr> <td>-92 dBm @ 6Mbps</td> <td>-97 dBm @ 1Mbps</td> </tr> <tr> <td>-74 dBm @ 54Mbps</td> <td>-89 dBm @ 11Mbps</td> </tr> </table>	<b>802.11g</b>	<b>802.11b</b>	-92 dBm @ 6Mbps	-97 dBm @ 1Mbps	-74 dBm @ 54Mbps	-89 dBm @ 11Mbps
<b>802.11g</b>	<b>802.11b</b>						
-92 dBm @ 6Mbps	-97 dBm @ 1Mbps						
-74 dBm @ 54Mbps	-89 dBm @ 11Mbps						
Available transmit power (Average power)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; text-align: center;">FCC</td> <td style="width: 50%; text-align: center;">ETSI</td> </tr> </table>	FCC	ETSI				
FCC	ETSI						

\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

	Frequency	Power	Frequency	Power
	2.412~2.462 GHz IEEE802.11g	26dBm@6~24Mbps 25dBm@36Mbps 23dBm@48Mbps 22dBm@54Mbps	2.412~2.472 GHz IEEE802.11g	26dBm@6~24Mbps 25dBm@36Mbps 23dBm@48Mbps 22dBm@54Mbps
	2.412~2.462 GHz IEEE802.11b	27dBm@1~11Mbps	2.412~2.472 GHz IEEE802.11b	27dBm@1~11Mbps
	Tolerance	±1 dBm	Tolerance	±1 dBm
Internal Antenna	Embedded 10dBi Panel antenna			
External Antenna	1* SMA connector			

Software Features	
General	
Topology	Infrastructure
Protocol / Standard	IEEE 802.3 (Ethernet) IEEE 802.3u (Fast Ethernet) IEEE 802.11b/g (2.4GHz WLAN)
Operation Mode	<b>802.11 b/g</b> Access Point Client Bridge Client Router
LAN	DHCP Server DHCP Client
VPN	VPN – pass through
Wireless	Channel Selection (Setting varies by countries) Transmission Rate 11 b/g : 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps Super G : 108 Mbps Long distance transmission : 1km to 30km

\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

	<p>Transmit power table</p> <p>Signal Strength indication using LEDs</p> <p>PPPoE(CR mode)</p>
Security	<p>WEP Encryption-64/128/152 bit</p> <p>WPA/WPA2 Personal (WPA-PSK using TKIP or AES)</p> <p>WPA/WPA2 Enterprise (WPA-EAP using TKIP)</p> <p>802.1x Authenticator</p> <p>Hide SSID in beacons</p> <p>802.1Q VLAN</p> <p>MAC address filtering, up to 50 field</p> <p>L2 isolation(AP mode)</p> <p>Wireless STA (Client) connected list</p> <p>Web-redirect</p>
QoS	WMM
Management	
Configuration	Web-based configuration (HTTP)
Firmware Upgrade	<ul style="list-style-type: none"> <li>- Upgrade firmware via web-browser</li> <li>- Keep latest setting when f/w update</li> </ul>
Administrator Setting	Administrator password change
Reset Setting	<ul style="list-style-type: none"> <li>- Reboot (Press 1 second)</li> <li>- Reset to Factory Default (Press 5 seconds)</li> </ul>
System monitoring	Status, Event Log
SNMP	V1, V2c
MIB	MIB I, MIB II (RFC1213) and Private MIB
Backup & Restore	Settings through Web
Time setting	<p>NTP (Auto-setting of time)</p> <p>Time setting manually</p>

## Environment & Mechanical

Temperature Range	<p>Operating -20°C~70°C</p> <p>Storage -30°C to 80°C</p>
-------------------	--

\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

Humidity (non-condensing)	0%~90% typical
Dimensions	260mm (L) x 84mm (W) x 55mm (H)
Weight	300g

\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

\*\* All specifications are subject to change without notice.


20080930\_V1.0

## Application

Access Point + Client Bridge scenario



Long Range Transmitting



\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

\*\* All specifications are subject to change without notice.

20080930\_V1.0

**Front**



**Rear**



**Pole mount**



\* Theoretical wireless signal rate based on IEEE standard of 802.11a, b, g chipset used. Actual throughput may vary. Network conditions and environmental factors lower actual throughput rate.

\*\* All specifications are subject to change without notice.

20080930\_V1.0