



ESW-8824

24-port Ethernet Switch



ESW-8824 is an easy installation 24-port Fast Ethernet switch for small/medium businesses and individuals with high performance. It's a perfect way to extend your network structure.

This 24 port Ethernet Switch doesn't require any configuration and software. So, it is very simple to install.

Have auto MDIX function support, so there is no need for crossover cables when you are connecting to another switch or to a computer.



Features	
Compliant with the IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX specifications	Supports Store & Forward architecture and performs forwarding and filtering
24 port 10/100Mbps TX Auto-Negotiation Ethernet Switch	Broadcast Storming Filter function
Full/Half-Duplex capability on each TX port	IEEE802.3x flow control for Full-duplex
Supports TP interface Auto MDIX function for auto TX/RX swap	Back Pressure function for Half-duplex operation
Automatic Source MAC Address Learning and Aging	Supports to handle up to 152 bytes packet
Supports up to 8K MAC addresses	LED indicators for simple diagnostics and management



ESW-8824

24-port Ethernet Switch



Specifications

Chip	RTL8324+RTL8208B
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3x Flow Control
Access Method	CSMA/CD
Network Media	10BASE -T: UTP Cat. 3 or up, 100BASE-TX: UTP Cat. 5 or up
Transmission Method	Store and Forward
Store and Forward	8K
Built-in Buffer	1.25M bits
Data Transfer Rate	10/100Mbps (Half-duplex), 20/200Mbps (Full-duplex)
Auto MDI/MDIX	YES
LED Indicators	Power, Link/Activity, speed

Environmental

Dimension	440mm(L) x 200mm(W) x 44mm(H)
Weight	2500g
Temperature	0° to 50° C (operating), -20° to 70° C (storage)
Humidity	5% to 90 % non-condensing (operating), 5% to 90% non-condensing (storage)
Certifications	FCC Part 15 Class A, CE Mark



EnGenius®

ESW-8824

24-port Ethernet Switch



Package Contents

- 24 port Ethernet Switch
- Power Cord
- Rock-mount kit
- CD with user guide